

# SANDVIK RH460g 8"

## COMPLETE HAMMER


4 1/2 BECO pin

32-4685-GQA-72C

WEIGHT		OUTSIDE DIAMETER		HAMMER LENGTH		HAMMER LENGTH WITH BIT			
						Bit closed		Bit extended	
kg	lb	mm	inch	mm	inch	mm	inch	mm	inch
244	537	194	7.64	1426	56.14	1566	61.65	1608	63.31

AIR CONSUMPTION, CFM			AIR CONSUMPTION, M <sup>3</sup> /MIN, DIN 1343			POWER OUTPUT (kW)	
150 psi	250 psi	350 psi	10 bar	18 bar	24 bar	24 bar	
365	852	1290	10.3	24.1	36.5	50	



REPLACEMENT PARTS ITEM DESCRIPTION	Weight, kg	Weight, lb	Part No.
<b>1. Top sub</b>			
4 1/2 BECO pin	57.0	125	BG00278298
2. Check valve dart no choke	0.80	1.76	BG00321984
3. Check valve spring	0.04	0.09	BG00652827
4. Make up ring	0.40	0.88	BG00015380
5. Air distributor with O-ring	9.40	20.7	BG00078615
6. O-ring air distributor			In seal kit
7. Inner cylinder	10.5	23.1	BG00057803
8. Piston	50.0	110	BG00277131
9. Piston case with retainer ring	94.2	207	BG00278268
10. Piston retainer ring	0.20	0.44	BG00096748
11. O-ring guide sleeve			In seal kit
12. Guide sleeve with O-ring	3.00	6.60	BG00096749
13. Bit retainer ring with O-ring	1.40	3.08	BG00096752
14. O-ring bit retainer ring			In seal kit
15. Driver sub hard faced	15.9	35.0	BG00303677
<b>Optional</b>			
Choke set, blank, 3mm, 4.5mm and 6mm	0.01	0.02	BG00081800
Check valve dart with choke hole	0.80	1.76	BG00015375
<b>Seal kit</b>			
1 piece of #6, #11 & #14	0.01	0.02	BG00303706
<b>Rebuild kit</b>			
1 piece of #1, #9, #15 & seal kit			
4 1/2 BECO pin	167	367	BG00305742
<b>Bit shank</b>			
QL80			

Sandvik Mining and Rock Technology reserves the right to make changes to the information on this data sheet without prior notification to users. Please contact a Sandvik representative for clarification on specifications and options.