

SANDVIK RH560g 4"

COMPLETE HAMMER

#24 Cubex Pin

32-5645-GTA-77S

WEIGHT		OUTSIDE DIAMETER		HAMMER LENGTH		HAMMER LENGTH WITH BIT			
kg	lb	mm	inch	mm	inch	Bit closed		Bit extended	
						mm	inch	mm	inch
48	105.6	105	4.1	1,016	40	1,106	43.5	1,140	44.9

AIR CONSUMPTION, CFM			AIR CONSUMPTION, M3/MIN, DIN 1343			
150 psi	250 psi	350 psi	10 bar	18 bar	24 bar	
237	441	597	6.7	12.5	16.9	



REPLACEMENT PARTS ITEM DESCRIPTION	Weight, kg	Weight, lb	Part No.
1. Top Sub			
#24 Cubex Pin	9.0	19.8	BG00906532
O-ring Top Sub			In seal kit
O-ring Check Valve Dart			In seal kit
Check Valve Dart no Choke	0.3	0.7	BG00904454
Check Valve Spring	0.04	0.1	BG00876172
Make Up Ring	0.1	0.2	BG00014825
Air Distributor with O-Ring	2.8	6.2	BG00377566
O-Ring Air Distributor			In seal kit
Inner Cylinder	2.6	5.7	BG00376970
Piston	8.5	18.7	BG00334820
Piston Case	19.5	42.9	BG00361296
O-Ring Guide Sleeve			In seal kit
Guide Sleeve with O-Ring	1.3	2.9	BG00334637
Bit Retainer Ring	0.2	0.4	BG00811287
Driver Sub	3.4	7.5	BG00803816

Seal Kit			
1 Piece of 2, 3, 8 & 12	0.01	0.02	BG00925938

Rebuild Kit			
1 piece of 1, 11, 15 & Seal Kit			

#24 Cubex Pin	32.0	70.4	BG00933225
---------------	------	------	------------

Bit shank

QLX560-4



Sandvik Mining and Rock Technology reserves the right to make changes to the information on this data sheet without prior notification to users. Please contact a Sandvik representative for clarification on specifications and options.